

Repairs

- Limit in-water maintenance and perform cleaning where debris can be captured and disposed of properly. Marina tenants should check with the harbor office, for the type of boat maintenance work that can be done in the slip.

Harbor Rules

§15-212-55 Small craft repairs, reconstruction or major modification. Minor repairs to small craft may be made at the assigned berth and shall be completed within thirty days. If repairs are estimated to, or actually do, require that the vessel be out of service for more than thirty days, prior approval shall be sought from the HCDA to initiate or complete the repairs in the harbor. Prior approval shall be sought from the HCDA for any repairs requiring the use of cranes, lifts, and any similar devices within the harbor. Repair, reconstruction or major modification that would interfere with the free flow of other vessels, pedestrian, or vehicle traffic shall only be accomplished in an area designated by the HCDA. Failure to seek approval as required by this section shall be grounds for the revocation of the revocable permit.

Sanding

- For sanding/painting jobs that involve less than 10% of the vessels surface, please follow the guidelines below. For large hull sanding/painting jobs, perform the work in dry dock, haul-out facility or any other location away from a waterbody.
- Cover areas between the boat and dock with plastic sheeting or a tarp to catch debris. Contain area of work properly with tarps. Reverse boat in the berth to work on the other side.
- Use a dust-less sander, which collects chips and dust and helps prevent the release of toxic materials and sweep or vacuum all residual sanding dust and put it in the trash can. Wipe down small amounts of sanding or other dust with a damp rag.
- Deploy a boom around the vessel or work area to ensure capture of the debris. It is your responsibility to capture any minor or light debris that accidentally escapes.
- Sanding in a heavy breeze is strictly prohibited.
- Vacuum, sweep and clean prior to moving tarps and clean often during the project. Dispose of waste materials PROPERLY!

Painting

- Cover side between the boat and the dock with plastic sheeting or a tarp to catch drips. Reverse the boat to work on the other side. Cover the prep area on the dock to catch drips.
- Mix only enough paint and thinner for the job. Seal containers tightly when not in use. Spills or drips on the dock will not be tolerated no matter how small.
- Painting in a heavy breeze is strictly prohibited.
- Spray painting at any time is strictly prohibited.
- Limit the amount of open solvents or paints on the dock to one gallon or less.
- Always mix paints or epoxy over a tarp.
- Always use a drip pan or drop cloth.